

# Sealgun Primer

Solvent based bituminous primer for bitumen sheet membranes



## Description

Sealgun Primer is a solvent based bituminous primer formulated for Sealgun line of products.

## Applications

Sealgun acts as a primer for masonry and concrete to improve the bonding of bituminous materials. It is used as a primer coat prior to the application of Sealgun bituminous membrane.

## Advantages

- ▲ Improves adhesion of Sealgun bituminous membrane on concrete and masonry surfaces.
- ▲ Seal Pores on substrates such as concrete.
- ▲ One component- easy to use.
- ▲ Cold applied, does not require heating or thinning.

## Standards

Conforms to ASTM D 41 – Asphalt primer for roofing, damp proofing and waterproofing.

## Method of Use

### Surface Preparation

The substrate should be sound, clean, dry and free from contaminations. Surface laitance should be removed by light scrubbing or grit blasting. Concrete should be cured for 8 days prior to the application of Sealgun Primer.

### Application

Sealgun Primer should be mixed thoroughly before use. Apply primer using brush, roller or spray at a rate 0.30 ltr/m<sup>2</sup> and allow it to dry for 24 hours.

## Packaging

Sealgun Primer is available in 20 and 200 ltr drums.

## Coverage

Sealgun Primer should be applied in one coat at approximately a rate of 0.30 ltr/m<sup>2</sup>, depending on the surface condition.

## Technical Properties:

Colour:	Black
Specific gravity:	0.90 ± 0.02
Water content:	0.20%
Service temperature:	5 to 50°C
Setting time:	24 hr @ 23°C
Flash point:	40°C

## Storage

Store in a cool and dry place, in air tight container, away from heat or direct sunlight.

If these conditions are exceeded, DCP Technical Department should be contacted for advise.

## Cautions

### Health and Safety

Apply in well ventilated areas. Do not smoke. Do not apply near naked flames. In closed areas use force ventilation and carbon active masks. Keep in mind that solvents are heavier than air so vapour concentration is higher in air closer to floor. Clean hands with warm soap and water after application.

For further information refer to the Material Safety Data Sheet.

### Fire

Sealgun Primer contains volatile flammable solvents.

# Sealgum Primer

## More from Don Construction Products

A wide range of construction chemical products are manufactured by DCP which include:

- ▲ Concrete admixtures.
- ▲ Surface treatments
- ▲ Grouts and anchors.
- ▲ Concrete repair.
- ▲ Flooring systems.
- ▲ Protective coatings.
- ▲ Sealants.
- ▲ Waterproofing.
- ▲ Adhesives.
- ▲ Tile adhesives and grouts.
- ▲ Building products.
- ▲ Structural strengthening.

**Note:**

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

